

Commander Site Controller



Verifone's Commander Site Controller offers convenience store owners a versatile site management solution providing increased speed in payment acceptance, fueling operations, and back-office store control. The Commander is certified across all major dispenser brands, payment networks, and oil brands. The solution features Commander's Configuration Client, a web-based tool that is used to modify and set up c-store configurations.

In addition to Configuration Client, Commander also has other site management software: Report Navigator, Transaction Manager and Commander Console. Report Navigator is used to view reporting data for the store. Reporting information such as the close day report can be configured to include a multitude of report options. Transaction Manager allows for site transaction logs and data to be accessed from the Commander or archived locally. Commander Console enables multiple store reporting data to be consolidated into one place for easy visibility to monitor and track sales trends.

The Commander's system architecture includes expansion slots to support up to 24 serial connections. It supports mixed dispenser brands and up to 64 fueling positions. Remote software upgrades are available to all Commander product lines using Verifone's Remote Software Delivery (VRSD) feature. Enabling our c-store customers to receive new software remotely, without requiring an onsite service technician.

Specifications

Site Controller

Memory

4GB DDR3 SDRAM, scalable to 8GB

Diagnostic Panel

Soft reset button, diagnostic console port, 7-segment status LEDs, heartbeat LED, power LED, diagnostic switches, add character based status display

Storage

Hard Disk Drive, 2.5" SATA, 250GB or Greater

Connectivity

1 × USB 2.0 ports; 2 × 10/100/1000 Ethernet ports; 16 × RS-232 serial ports, scalable to 24 ports

Processor

2.10 GHz Intel Core i3-2310E CPU, scalable to Intel Core i7

Communications

DTR power; Diagnostic Panel for fast debugging

Operating System

Secure real-time Linux, backup battery for power loss protection

Expansion Capability

PCIe expansion slot to add an additional 8 port serial card for up to 24 serial connections

Environmental

0° C to 40° C operating temperature

Physical

14.75" W × 6.25" H × 16" L

Commander Dashboard

Minimum System Requirements

Commander Site Controller Base 38, broadband connection

Browser

Supports Internet Explorer 10 and higher, Mozilla Firefox 4.0 and higher, Google Chrome, Safari

Mobile Device

Supports mobile devices with screens 7.5" and larger

Operating Systems

Windows and iOS